

Multipipe® PVC-U Cement

Properties	
Color	Colorless
Smell	Characteristic
Gap filling properties	0.1 mm- 1 mm
Viscosity	2000-3000 cPs
Density	0.9 g/cm ³
Solid matter	21 ± 1 %
Temperature resistance	-30 °C to 60 °C
Flammability	Flammable

Description

A premium quality, clear color, medium strength adhesive formulated for PVC and uPVC fitting and pipe bonding applications. It is easy to use, fast setting, and offers superior bonding strength.

Direction for use:

- The surfaces to be bonded must be clean, and free of dust and grease. The surfaces can be lightly roughed with sandpaper.
- Stir the adhesive well. Apply a uniform coating using a brush. First to the inside of the socket and then to the pipe.

- Join immediately. (Do not allow a skin to form).
- Hold together for 10 seconds and wipe off the excess adhesive.
- Wait 24 hours before subjecting the pipe to pressure.

Application

Multipipe® can be used to join PVC pipes for pressure and non-pressure applications. The bond is flexible, waterproof, and resistant to heat, and pressure and can be used for electrical conduits, gas piping, and water pipes

Storage and Handling

Store in a cool, dry place. Strict batch rotation must be observed.

Shelf life: The life of an unopened container, stored correctly, is 12 months (tubes) and 24 months (tins). Exposure to high temperatures shortens the shelf life.

Safety

Keep the lid closed at all times. The solvent vapors are flammable, and don't smoke or work near machinery that produces sparks.

Pack size

100 mL tube

250 mL can